

Model OT-DWDM-4-2 4-Channel 200GHz DWDM

Features / Benefits



APPLICATIONS

- DWDM Transmission System
- Optical Fiber Device
- Optical Fiber Amplifier System
- Wideband Networks

FEATURES

- Epoxy Free
- Low Insertion Loss
- High Reliability and Stability
- Polarization Independent

Operating Specifications

Parameter	Units	Specification	
		Mux	Demux
Center Wavelength (λ_c)	nm	ITU Channel ± 0.1	
Channel Spacing	GHz	200	
0.5 dB Pass Band	nm	± 0.36	
Typ. Insertion Loss	dB	1.8	
Max. Insertion Loss	dB	2.2	
Max. Channel Uniformity	dB	1.2	
Min. Isolation of Adjacent Ch.	dB	N/A	25
Min. Isolation of Non-Adjacent Ch.	dB	N/A	40
Min. Directivity	dB	55	
Max. Polarization Dependent Loss	dB	0.15	
Min. Return Loss	dB	45	
Max. Polarization Mode Dispersion	ps	0.1	
Max. Thermal Stability	dB/°C	0.006	
Max. Thermal Wavelength Drift	nm/°C	0.002	
Max. Optical Power	mW	250	
Operating Temperature	°C	0 to +65	
Storage Temperature	°C	-40 to +85	
Package Dimensions	mm	O: 100 x 80 x 9 T: 19" 1RU Rack Z: 140 x 35 x 194	

Ordering Information

Standalone

OT-DWDM-4-2------

- Function
M = Mux D = Demux
- Beginning Channel
Refer to ITU Frequency Guide
- Pigtail
2 = 2mm Cable
3 = 3 mm Cable
5 = 0.9 mm Loose Tube
- Package (mm)
O = 100 x 80 x 9
- Pigtail Length
05 or 10 = 0.5 or 1.0 Meters
- Connector
FA = FC/APC
SA = SC/APC

OT-DWDM-4-2----

OTCP & Rack

- Function
M = Mux D = Demux
- Beginning Channel
Refer to ITU Frequency Guide
- Package (mm)
T = 1RU 19" Rack
Z = Olson OTCP Housing
- Connector
FA = FC/APC
SA = SC/APC

Data sheets and performance may be updated without notice.